

### PRD N° 0230 B

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC





### **EU Type Examination Certificate**

Date: 2021/06/30 n. 860212606/TE Validity: 2026/06/29

This Certificate is a translation in English of the original Certificate issued in Italian.

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health <mark>req</mark>uirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	U-GROUP SRL Via Borgomanero, 50 – 28040 Paruzzaro (NO) – Italia		
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials)		
Category of PPE:	II: "medium" risks.  This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.		
Model:	"DIICH ECD"		

RUSH ESD code RS20164

Description:

model: A (low-footwear);

fastening system: by means of black laces;

processing: direct injection;

outsole: grey 63354 compact PU "7466 360" marked "ANTISTATIC OIL RESISTANT"

(CH00116);

midsole: black foam PU (CH00117) with white polystyrene inserts in the rear area;

upper: black Nabuk Bottalato leather declared thickness 1,8/2,0 mm (PL00066), with black polymeric insert in the heel area, marked "BREATHABLE", with lateral holes closed by means of a fabric/membrane;

rear collar: black grey Lycra MOREA (\$100753) padded with a black folded Lycra edge (AT01766); the collar has been shaped to create a loop to ease the donning;

tongue: black fabric ALBANY semplice (\$100046), lined and padded;

bellows: black coated synthetic fabric SPICE (S100002);

vamp lining: grey three-dimensional fishnet knitting IMOLA coupled with black canvas (SI00649);

quarter lining: grey 599 three-dimensional perforated fishnet knitting SURF (SI00468);

tongue lining: black three-dimensional perforated fishnet knitting SURF (S100466);

rear collar lining: black three-dimensional perforated fishnet knitting SURF, reversed (SI00466);

heel- grip lining: anthracite grey non-woven fabric THORIN (\$100283);

insole: white multilayered fabric with a black print declared conductive, art. WB FLEX (SP00007), which also serves as penetration resistant insert;

removable insock: grey perforated foam material coupled with a black knitting with "WOW!" stamp in contact with the user, with zig-zag stitching with conductive thread in the forepart (TL00161);

toecap: aluminium, art. A522 MARTEK (PU00041).

Optional interchangeable orthopedic insocks (DGUV 112-191) described by the Customer as follows (see also page 3): SECOSOL® by Matthias Hartmann Orthopädie + Sport GmbH (max thickness in the toetip area: 2,9 mm):

SECOSOL® COMPLETE – article number 951622012451XX

SECOSOL® LAMINATO CON TESSUTO – article number 9516101XXX7XXX





Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





# EU Type Examination Certificate

Date: 2021/06/30 n. **860212606/TE** Validity: 2026/06/29

Technical Standard:	EN ISO 20344:2011 (UNI EN ISO 20344:2012) EN ISO 20345:2011 (UNI EN ISO 20345:2012)	Personal protective equipment – Test methods for footwear  Personal protective equipment – Safety footwear	
Intended use:	general industry, engineering industry, construction industry, agriculture, warehouse works on trucks, cranes.		
Size range:	from 35 to 48		
Technical File:	DC-13572/E		
Test repo <mark>rt:</mark>	RCT n°4031906/E		
Functions and performance levels:	basic requirements for safet mandatory ones, among wh	ty footwear (SB) (see Table 2 and 3 of EN ISO 20345:2011): a hich:	
	<ul> <li>SRC = Slip resistance – meets the following requirement:</li> <li>surface: ceramic / <u>lubricant</u>: detergent solution;</li> <li>surface: steel / <u>lubricant</u>: glycerol.</li> </ul>		
	Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011):  \$3 = closed seat region, antistatic properties, energy absorption of seat region resistance to fuel oil, water penetration resistance and absorption (water-repeller upper), penetration resistance, cleated outsole; CI = cold insulation of the outsole.		
	diameter of the perforating ob ergonomics advantages (flexib Note 2: the footwear also meet	ince of the synthetic stitch proof insole tends to decrease with the ject; in return the synthetic insole offers more protective surface and illity, insulation, humidity and impact absorption). Its the requirement in accordance with IEC 61340-5-1:2016 (IEC 61340 ance ESD (electric dissipative footwear).	
Marking:	<ul> <li>CE Marking;</li> <li>registered trademark, nan</li> <li>designation of the footwe</li> <li>nr. and year of the Stando</li> <li>size of the footwear (printe</li> <li>production date (month +</li> </ul>		





### DBD No 0330 B

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





## **EU Type Examination Certificate**

Date: 2021/06/30 n. **860212606/TE** Validity: 2026/06/29



www.u-power.it

UGROUP RS20164

05/2021 RUSH ESD

EN ISO 20345:2011 S3 CI SRC

### MADE IN TUNISIA

UGROUP SRL Via Borgomanero,50 Paruzzaro (NO)-Italy

DPI II



### SECOSOL® COMPLETE 951622012451XX



## SECOSOL® LAMINATO CON TESSUTO 9516101XXX7XXX



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements.

The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

