

According to the Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

A.N.C.I. Servizi s.r.l. a socio unico – CIMAC Laboratories
Community Identification N° 0465

Grants:
Manufacturer
U GROUP S.R.L.
VIA BORGOMANERO 50
28040 PARUZZARO

EU TYPE-EXAMINATION CERTIFICATE MODULE B
N° F-108-01406-18 Rev. 2

for the following model of Personal Protective Equipment:

Design/Item: Low shoe art. LI30076 JAKE ESD
Category of PPE: II
Additional requirements: S1 P SRC

safety footwear for professional use according to harmonized standard (*)
EN ISO 20345:2011

Picture of the basic model



First issue date: 13/12/2018
Revision date: 27/08/2020
Expiry date: 13/12/2023

Technical Manager
Giuseppe Bellotti



| | | | |
|--|---|-----|-------------------------|
| Manufacturer's identification mark: | LUPOS | | |
| Classification: | I - Footwear made from leather and other materials, excluding all-rubber or all-polymeric footwear | | |
| Size range: | from 35 to 48 (french point) | | |
| Identification of last: | 7466 UP55 | | |
| Manufacturing process: | Injection | | |
| The footwear has a: | metallic toecap | cod | PU00041 (MARTEK 522) |
| | non-metallic penetration-resistant insert | cod | SP00007 (LENZI WB FLEX) |
| | removable insock | cod | TL00149 |
| | | | SECOSOL 951622012451XX |
| | | | SECOSOL 9516101XXX7XXX |
| Additional requirements: | heel area closed; A antistatic properties; E energy absorption of seat region; P penetration resistance of sole complex; FO fuel oil resistant outsole; cleated outsole. | | |

Test Reports: The results of tests and examinations are contained in the following test reports:

| | | | | |
|-------------------------------------|-------|---------------------|-------|------------|
| Whole footwear | CIMAC | RP 2019/2554-3-RP-2 | dated | 07/10/2019 |
| Bottom of the footwear | CIMAC | RP 2020/0920-1-RP-1 | dated | 06/04/2020 |
| | CIMAC | RP 2020/0920-2-RP-1 | dated | 06/04/2020 |
| | CIMAC | RP 2020/0920-3-RP-1 | dated | 06/04/2020 |
| Upper | CIMAC | RP 2017/2474-3-RP-2 | dated | 15/12/2017 |
| | CIMAC | RP 2017/2474-3-RP-3 | dated | 15/12/2017 |
| | CIMAC | RP 2017/2474-3-RP-4 | dated | 15/12/2017 |
| Toecap | CIMAC | RP 2020/0196-1-RP-1 | dated | 29/01/2020 |
| Quarter lining | CIMAC | RP 2018/1150-1-RP-2 | dated | 15/06/2018 |
| | CIMAC | RP 2018/1150-1-RP-4 | dated | 15/06/2018 |
| Tongue/Penetration-resistant insert | CIMAC | RP 2017/1071-1-RP-2 | dated | 01/06/2017 |
| | CIMAC | RP 2017/1071-1-RP-3 | dated | 01/06/2017 |
| | CIMAC | RP 2017/1071-1-RP-4 | dated | 01/06/2017 |
| Removable insock | CIMAC | RP 2019/0916-3-RP-2 | dated | 12/04/2019 |
| | CIMAC | RP 2019/0916-3-RP-4 | dated | 12/04/2019 |
| | CIMAC | RP 2017/2742-1-RP-2 | dated | 19/12/2017 |
| Outsole/Vamp lining | CIMAC | RP 2018/2573-1-RP-2 | dated | 13/12/2018 |
| | CIMAC | RP 2018/2573-1-RP-3 | dated | 13/12/2018 |
| | CIMAC | RP 2018/2573-1-RP-4 | dated | 13/12/2018 |

Marking

CE Marking 

Name and postal address of the Manufacturer
manufacturer's type designation
the number and year of the reference European standard
Category and additional requirements of the PPE
Month and year of fabrication
Size
Batch number

(*) Subsystems and safety components which are in conformity with harmonised standards or parts thereof the references of which have been published in the Official Journal of the European Union shall be presumed to be in conformity with the essential requirements set out in Annex II Regulation (EU) 2016/425.

Validity conditions: This certificate is valid for 5 years from the date of issue. On expiration the manufacturer shall ask for its renewal. The rules applied are those in force on the date of issue shown on this certificate; The validity of the certificate is no longer guaranteed if substitutive standards are issued before the expiration date. All changes made to the model and to the materials described in this EU type-examination certificate shall be reported to and approved by CIMAC. This EC Type-Examination Certificate may be integrally duplicated; the copy must be faithful, legible (if pint size) and must contain the bold caption "TRUE COPY". This certificate must be kept by the manufacturer to be shown, on request, to the inspection or notifying authorities.