

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC





EU Type Examination Certificate

Date: 2021/05/24 n. 860212103/TE Validity: 2026/05/23

This Certificate is a translation in English of the original Certificate issued in Italian.

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health <mark>req</mark>uirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: **U-GROUP SRL** (Responsible of the Via Borgomanero, 50 – 28040 Paruzzaro (NO) – Italia PPE) Type of PPE: Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials) Category of PPE: II: "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.

Model: "DOMINGO" code RI11034

Description: model: B (ankle boot);

fastening system: by means of laces;

processing: direct injection;

outsole: yellow compact rubber "7466 NIC HRO" marked "ANTISTATIC OIL RESISTANT" (Al00149);

midsole: black "7466 NIC UK" foam PU (CH00117), which also serves as reinforcement of

the toe-end;

<u>upper</u>: black fabric with yellow and grey polymeric threads coupled with a bl<mark>ack felt</mark> PUTEK PLUS FF WR FELTRO 350 (SI00736) and black coated microfiber ANTIABRASION

MICRO.LARICI declared thickness 2,0 mm (SI00544) in the fastening area; bellows: black coated synthetic fabric SPICE (S100002);

tongue: black fabric ALBANY (\$100046), centrally lined and padded;

vamp lining: light grey three-dimensional fishnet knitting IMOLA coupled with black

canvas (SI 00649);

guarter and heel-grip lining: yellow three-dimensional fishnet knitting SURF (S100485);

insole: white multilayered fabric with a black print declared conductive art. WB FLEX

(SP00007), which also serves as penetration resistant insert;

removable insock: black perforated foam material coupled with a green knitting with "WOW!" stamp in contact with the user, with zig-zag stitching with conductive thread in

the forepart WOW 2 (TL00162);

toecap: polymeric material, art. PS240 HAWAI (PU 00042).

Optional interchangeable orthopedic insocks (DGUV 112-191) described by the Customer as follows (see also page 3): SECOSOL® by Matthias Hartmann Orthopädie +

Sport GmbH (max thickness in the toetip area: 2,9 mm): SECOSOL® COMPLETE – article number 951622012451XX

SECOSOL® LAMINATO CON TESSUTO – article number 9516101XXX7XXX

Technical Standard: EN ISO 20344:2011 Personal protective equipment – Test methods for footwear

> (UNI EN ISO 20344:2012) EN ISO 20345:2011 (UNI EN ISO 20345:2012)

Personal protective equipment – Safety footwear



DBD No 0330 B

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2021/05/24 n. **860212103/TE** Validity: 2026/05/23

	, , , , , , , , , , , , , , , , , , ,
Intended use:	general industry, engineering industry, construction industry, agriculture, warehouses, works on trucks, cranes.
Size range:	from 38 to 47
Technical File:	DC-13299/E
Test report:	RCT n°4031704/E
Functions and performance levels:	basic requirements for safety footwear (SB) (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which:
	 SRC = Slip resistance – meets the following requirement: surface: ceramic / <u>lubricant</u>: detergent solution; surface: steel / <u>lubricant</u>: glycerol.
	Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011): \$3 = closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, water penetration resistance and absorption (water-repellent upper), penetration resistance, cleated outsole; HRO = resistance to hot contact of the outsole; HI = heat insulation of sole complex; CI = cold insulation of the outsole.
	Note: the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption).
Marking:	on a stitched label and displaying the following information: - CE Marking; - registered trademark, name and complete address of the Manufacturer; - designation of the footwear (= article name and alphanumeric code); - nr. and year of the Standard of reference + safety symbols; - size of the footwear (printed on the outsole); - production date (month + year);

- additional information: website, category of the PPE, "Made in ...".





PRD Nº 0230 B

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2021/05/24 n. **860212103/TE** Validity: 2026/05/23



www.u-power.it

RI11034 UGROUP

03/2021 DOMINGO

EN ISO 20345:2011 S3 HRO HI CI SRC

MADE IN TUNISIA

UGROUP SRL Via Borgomanero,50 Paruzzaro (NO)-Italy

DPI II





SECOSOL® COMPLETE 951622012451XX



SECOSOL® LAMINATO CON TESSUTO 9516101XXX7XXX



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements.

The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).