



# EU Type Examination Certificate


Date: 2023/06/23

n. **860232515/TE**

Validity: 2028/06/22

This Certificate cancels the previous one n° 860212105/TE dated 2021/05/24 and is a translation in English of the original Certificate issued in Italian.

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	<b>U-GROUP SRL</b> Via Borgomanero, 50 – 28040 Paruzzaro (NO) – Italia	
Type of PPE:	<b>Safety footwear</b> in conformity with <b>EN ISO 20345:2011 class I</b> (= footwear in leather and other materials)	
Category of PPE:	<b>II</b> : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.	
Model	<b>"FUERTE"</b> code <b>RI21314</b>	
Description:	 <p><u>model</u>: A (low footwear);  <u>fastening system</u>: by means of laces;  <u>processing</u>: direct injection;  <u>outsole</u>: grey compact rubber 7466 NIC HRO marked "antistatic oil resistant" (AI00154);  <u>midsole</u>: black 7466 NIC UK foam PU (CH00117);  <u>upper</u>: black split grained leather MINA IDRO declared thickness 1,8/2,0 mm (PL00010) and grey retro-reflective insert, art. LUXOR ARGENTO ECO, in the heel area (SI00245);  <u>collar</u>: black coated synthetic fabric, art. SPICE (SI00002), padded;  <u>bellows and tongue</u>: black coated synthetic fabric, art. SPICE (SI00002), centrally lined and padded;  <u>vamp lining</u>: grey three-dimensional fishnet knitting coupled with black canvas (SI00743);  <u>rear and heel-grip lining</u>: grey col. 599 three-dimensional knitting, art. SURF (SI00468);  <u>tongue and rear collar lining</u>: blue Royal colour three-dimensional fishnet knitting, art. SURF (SI00259);  <u>insole</u>: white multi-layered fabric with black print declared conductive, art. WB FLEX (SP 00007), which also serves as penetration resistant insert;  <u>removable insock</u>: black perforated foam material coupled with green knitting with "WOW!" stamp in contact with the user, with zig-zag stitching with conductive thread in the forepart, art. WOW 2 (TL 00162);  <u>toecap</u>: polymeric material, art. PS240 HAWAI (PU 00042).</p> <p><u>Optional interchangeable orthopedic insocks (DGVV 112-191)</u> described by the Customer as follows (see also page 3): SECOSOL® by Matthias Hartmann Orthopädie + Sport GmbH (max thickness in the toetip area: 2,9 mm):  SECOSOL® COMPLETE – article number 951622012451XX  SECOSOL® LAMINATO CON TESSUTO – article number 9516101XXX7XXX</p>	
Technical Standard:	<b>EN ISO 20344:2011</b> (UNI EN ISO 20344:2012) <b>EN ISO 20345:2011</b> (UNI EN ISO 20345:2012)	Personal protective equipment – Test methods for footwear  Personal protective equipment – Safety footwear





# EU Type Examination Certificate

Date: 2023/06/23

n. **860232515/TE**

Validity: 2028/06/22

Intended use:	general industry, engineering industry, agriculture, warehouses, works on trucks, cranes.
Size range:	from 38 to 47
Technical File:	<b>DC-16945/E</b>
Test report:	<b>RCT n°4251907.01/E</b>
Functions and performance levels:	<p><b>basic requirements for safety footwear</b> (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which:</p> <p><b>SRC = Slip resistance</b> – meets the following requirements:            - <u>surface</u>: ceramic / <u>lubricant</u>: detergent solution;            - <u>surface</u>: steel / <u>lubricant</u>: glycerol.</p> <p><b>Additional requirements</b> (Tab. 18 and 20 of EN ISO 20345:2011):  <b>S3</b> = closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, water penetration resistance and absorption (water-repellent upper), penetration resistance, cleated outsole; <b>CI</b> = cold insulation of the outsole; <b>HI</b> = heat insulation of outsole complex; <b>HRO</b> = resistance to hot contact of the outsole.</p> <p>Note: the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption).</p>
Marking:	<p>on a stitched label and displaying the following information:</p> <ul style="list-style-type: none"> <li>- <b>CE Marking</b>;</li> <li>- registered trademark, name and complete address of the Manufacturer;</li> <li>- designation of the footwear (= article name and alphanumeric code);</li> <li>- nr. and year of the Standard of reference + safety symbols;</li> <li>- size of the footwear (printed on the outsole);</li> <li>- production date (month + year);</li> <li>- additional information: website, category of the PPE, "Made in ...".</li> </ul>





## EU Type Examination Certificate

Date: 2023/06/23

n. **860232515/TE**

Validity: 2028/06/22

**CE**  
**U-Power**  
Don't worry... be happy!  
www.u-power.it

**UGROUP**  
**RI21314**

**05/2023**  
**FUERTE**

**EN ISO 20345:2011**  
**S3 CI HI HRO SRC**

**MADE IN TUNISIA**

UGROUP SRL  
Via Borgomanero, 50  
Paruzzaro (NO)-Italy

**DPI II**



**SECOSOL® COMPLETE**  
**951622012451XX**



**SECOSOL® LAMINATO CON TESSUTO**  
**9516101XXX7XXX**



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements.  
The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

