

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC





### **EU Type Examination Certificate**

Date: 2021/06/30 n. 860212603/TE Validity: 2026/06/29

This Certificate is a translation in English of the original Certificate issued in Italian.

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health <mark>req</mark>uirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	U-GROUP SRL Via Borgomanero, 50 – 28040 Paruzzaro (NO) – Italia		
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials)		
Category of PPE:	"medium" risks. is certificate is based on reference standards listed below: its validity is no longer assured should new version of the standards come into force.		
Model:	"DARYL ESD"		

DARYL ESD code RS10084

model: B (ankle boot); Description:

fastening system: by means of neon green laces;

processing: direct injection;

outsole: grey 63354 compact PU "7466 360" marked "ANTISTATIC OIL RESISTANT"

(CH00116);

midsole: black foam PU (CH00117) with white polystyrene inserts in the rear area;

upper: lead-grey color Nabuk Bottalato leather declared thickness 1,8/2,0 mm (PL00067), with a black polymeric insert in the heel area, marked "BREATHABLE", with

lateral holes closed by means of a fabric/membrane; collar: grey 14 fabric ALBANY coupled with PE (\$100092);

tongue: grey 14 fabric ALBANY semplice (S100093), lined and padded;

bellows: black coated synthetic fabric SPICE (S100002);

vamp lining: grey three-dimensional fishnet knitting IMOLA coupled with black canvas

guarter lining: grey 599 three-dimensional perforated fishnet knitting SURF (S100468);

rear collar and tongue lining; fluo-green three-dimensional perforated fishnet knitting SURF (SI00206);

insole: white multilayered fabric with a black print declared conductive, art. WB FLEX (SP00007), which also serves as penetration resistant insert;

removable insock: grey perforated foam material coupled with black knitting with "WOW!" stamp in contact with the user, with zig-zag stitching with conductive thread in the forepart (TL00161);

toecap: aluminium, art. A522 MARTEK (PU00041).

Optional interchangeable orthopedic insocks (DGUV 112-191) described by the Customer as follows (see also page 3): SECOSOL® by Matthias Hartmann Orthopädie + Sport GmbH (max thickness in the toetip area: 2,9 mm):

SECOSOL® COMPLETE – article number 951622012451XX

SECOSOL® LAMINATO CON TESSUTO – article number 9516101XXX7XXX







### DBD No 0330 B

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





# EU Type Examination Certificate

Date: 2021/06/30 n. **860212603/TE** Validity: 2026/06/29

Technical Standard:	EN ISO 20344:2011 (UNI EN ISO 20344:2012) EN ISO 20345:2011	Personal protective equipment – Test methods for footwea  Personal protective equipment – Safety footwear	
	(UNI EN ISO 20345:2012)	r elsonal profective equipment – safety tootwear	
Intended use:	general industry, engineer <mark>ing indu</mark> stry, construction ind <mark>ust</mark> ry, agriculture, warehouse works on trucks, cranes.		
Size range:	from 35 to 48		
Technical File:	DC-13569/E		
Test repo <mark>rt:</mark>	RCT n°4031903/E		
Fu <mark>nctions and</mark> perfor <mark>mance</mark> levels:	basic requirements for safety footwear (SB) (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which:		
	<ul> <li><u>surface</u>: ceramic / <u>lubric</u></li> <li><u>surface</u>: steel / <u>lubricant</u></li> </ul>		
	<b>S3</b> = closed seat region, antistatic properties, energy absorption of seat region resistance to fuel oil, water penetration resistance and absorption (water-repeller upper), penetration resistance, cleated outsole; <b>C1</b> = cold insulation of the outsole.		
	diameter of the perforating of ergonomics advantages (flex Note 2: the footwear also me	tance of the synthetic stitch proof insole tends to decrease with the object; in return the synthetic insole offers more protective surface and ibility, insulation, humidity and impact absorption).  ets the requirement in accordance with IEC 61340-5-1:2016 (IEC 61340 istance ESD (electric dissipative footwear).	
Marking:	<ul> <li>CE Marking;</li> <li>registered trademark, not</li> <li>designation of the footw</li> <li>nr. and year of the Stance</li> <li>size of the footwear (pringle production date (month)</li> </ul>		





### DBD No USSU B

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





## **EU Type Examination Certificate**

Date: 2021/06/30 n. **860212603/TE** Validity: 2026/06/29



www.u-power.it

UGROUP RS10084

05/2021 DARYL ESD

EN ISO 20345:2011 S3 CI SRC

### MADE IN TUNISIA

UGROUP SRL Via Borgomanero,50 Paruzzaro (NO)-Italy

DPI II



### SECOSOL® COMPLETE 951622012451XX



## SECOSOL® LAMINATO CON TESSUTO 9516101XXX7XXX



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements.

The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

