

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC





EU Type Examination Certificate

Date: 2021/07/07 n. 860212703/TE Validity: 2026/07/06

This Certificate is a translation in English of the original Certificate issued in Italian.

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health <mark>req</mark>uirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	U-GROUP SRL Via Borgomanero, 50 – 28040 Paruzzaro (NO) – Italia Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials)		
Type of PPE:			
Category of PPE:	II: "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.		
Model:	"IACOB ESD"		

fastening system: by means of grey laces;

processing: direct injection;

modello: B (ankle boot);

outsole: grey 63554 compact PU "7466 360" marked "ANTISTATIC OIL RESISTANT"

code RS10134

(CH00116):

midsole: black foam PU (CH00117) with white polystyrene inserts in the rear area;

outer toetip: made of the same material as that of the midsole;

<u>upper</u>: black fabric with grey polymeric threads coupled with black felt P<mark>UTEK STAR</mark> NERO FF BETA PLUS 350 S3 (S100752) with black coated microfiber MYCRO RUBBER NERO IDRO 2,1/2,2 mm (SI00707); on the fastening and on the heel area; with black polymeric insert in the heel area, marked "BREATHABLE", with lateral holes closed by means of fabric/membrane;

<u>collar</u>: black fabric ALBANY coupled with PE (\$100047);

tongue: black fabric ALBANY semplice (\$100046), lined and padded;

bellows: black coated synthetic fabric SPICE (S100002);

vamp lining: grey three-dimensional fishnet knitting IMOLA coupled with black canvas

guarter lining: black three-dimensional perforated fishnet knitting SURF (S100466);

tongue and rear collar lining: grey 599 three-dimensional perforated fishnet knitting SURF

insole: white multilayered fabric with a black print declared conductive, art. WB FLEX (SP00007), which also serves as penetration resistant insert;

removable insock: grey perforated foam material coupled with black knitting with "WOW!" stamp in contact with the user, with zig-zag stitching with conductive thread in the forepart (TL00161);

toecap: aluminium, art. A522 MARTEK (PU00041).

Optional interchangeable orthopedic insocks (DGUV 112-191) described by the Customer as follows (see also page 3): SECOSOL® by Matthias Hartmann Orthopädie + Sport GmbH (max thickness in the toetip area: 2,9 mm):

SECOSOL® COMPLETE – article number 951622012451XX

SECOSOL® LAMINATO CON TESSUTO – article number 9516101XXX7XXX



Description:





DBD No 0330 B

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2021/07/07 n. **860212703/TE** Validity: 2026/07/06

Technical Standard:	EN ISO 20344:2011 (UNI EN ISO 20344:2012)	Personal protective equipment – Test methods for footwear	
	EN ISO 20345:2011 (UNI EN ISO 20345:2012)	P <mark>er</mark> sonal protective equipment – Safety footwear	
Intended use:		wine in duration, a complex patients in all returns a complex particular to the complex particul	
inieriaea ose.	works on trucks, cranes.	ering industry, construction industry, agriculture, warehouses,	
Size range:	from 35 to 48		
Technical File:	DC-13609/E		
Test repo <mark>rt:</mark>	RCT n°4031911/E		
Functions and performance levels:	basic requirements for safe mandatory ones, among v	ety footwear (SB) (see Table 2 and 3 of EN ISO 20345:2011): all which:	
	SRC = Slip resistance – meets the following requirement:		
	- <u>surface</u> : ceramic / <u>lubricant</u> : detergent solution;		
	- <u>surface</u> : steel / <u>lubricant</u> :	: glycerol.	
	Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011):		
	\$3 = closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, water penetration resistance and absorption (water-repellent		
		ince, cleated outsole; CI = cold insulation of the outsole.	
	diameter of the perforating o	tance of the synthetic stitch proof insole tends to decrease with the bject; in return the synthetic insole offers more protective surface and	
		ibility, insulation, humidity and impact absorption). ets the requirement in accordance with IEC 61340-5-1:2016 (IEC 61340-	
		istance ESD (electric dissipative footwear).	
Marking:	on a stitched label and dis	splaying the following information:	
	•	ame and complete address of the Manufacturer;	
	- designation of the footwear (= article name and alphanumeric code);		
	- nr. and year of the Stanc	dard of reference + safety symbols;	
	- size of the footwear (prin		
	 production date (month additional information; w 	vebsite, category of the PPE, "Made in".	
	addinorial information. V	. same, salegoly of more 2, made in	





DBD No 0330 B

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2021/07/07 n. **860212703/TE** Validity: 2026/07/06



www.u-power.it

UGROUP RS10134

05/2021 JACOB ESD

EN ISO 20345:2011 S3 CI SRC

MADE IN TUNISIA

UGROUP SRL Via Borgomanero,50 Paruzzaro (NO)-Italy

DPI II





SECOSOL® COMPLETE 951622012451XX



SECOSOL® LAMINATO CON TESSUTO 9516101XXX7XXX



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements.

The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).