

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC





EU Type Examination Certificate

Date: 2021/06/30 n. 860212605/TE Validity: 2026/06/29

This Certificate is a translation in English of the original Certificate issued in Italian.

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health <mark>req</mark>uirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: **U-GROUP SRL** (Responsible of the Via Borgomanero, 50 – 28040 Paruzzaro (NO) – Italia PPE) Type of PPE: Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials) Category of PPE: II: "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.

Model: "RICK ESD" code **RS20224**

Description:

model: A (low-footwear);

fastening system: by means of yellow laces;

processing: direct injection;

outsole: grey 63354 compact PU "7466 360" marked "ANTISTATIC OIL RESISTANT"

(CH00116);

midsole: black foam PU (CH00117) with white polystyrene inserts in the rear area;

upper: black Nabuk Bottalato leather declared thickness 1,8/2,0 mm (PL00066), with black polymeric insert in the heel area, marked "BREATHABLE", with lateral holes closed by means of a fabric/membrane;

rear collar: dark grey Lycra MOREA (\$100753) padded with black folded Lycra edge (AT01766); the collar has been shaped to create a loop to ease the donning;

tongue: black fabric ALBANY semplice (\$100046), lined and padded;

bellows: black coated synthetic fabric SPICE (S100002);

vamp lining: grey three-dimensional fishnet knitting IMOLA coupled with black canvas (SI00649);

quarter lining: grey 599 three-dimensional perforated fishnet knitting SURF (SI00468);

tongue lining; yellow three-dimensional perforated fishnet knitting SURF (SI00485);

rear collar lining: yellow three-dimensional perforated fishnet knitting SURF, reversed (SI00485);

heel- grip lining: anthracite grey non-woven fabric THORIN (S100283);

insole: white multilayered fabric with a black print declared conductive, art. WB FLEX (SP00007), which also serves as penetration resistant insert;

removable insock: grey perforated foam material coupled with black knitting with "WOW!" stamp in contact with the user, with zig-zag stitching with conductive thread in the forepart (TL00161);

toecap: aluminium, art. A522 MARTEK (PU00041).

Optional interchangeable orthopedic insocks (DGUV 112-191) described by the Cust<mark>ome</mark>r as follows (see also page 3): SECOSOL® by Matthias Hartmann Orthopädie + Sport GmbH (max thickness in the toetip area: 2,9 mm):

SECOSOL® COMPLETE – article number 951622012451XX

SECOSOL® LAMINATO CON TESSUTO – article number 9516101XXX7XXX



Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2021/06/30 n. **860212605/TE** Validity: 2026/06/29

Technical Standard:	EN ISO 20344:2011 Personal pro (UNI EN ISO 20344:2012)	otective equipment – Test methods for footwear
	EN ISO 20345:2011 Personal pro	otective equipment – Safety footwear
	(UNI EN ISO 20345:2012)	
Intended use:	ge <mark>ne</mark> ral industry, engineer <mark>ing indus</mark> try, construction ind <mark>ustr</mark> y, agriculture, warehouses	
	works on trucks, cranes.	
Size range:	from 35 to 48	
Technical File:	DC-13571/E	
Test report:	RCT n°4031905/E	
basic requirements for safety footwear (SB) (see Table 2 and 3 of EN erformance levels: mandatory ones, among which:		SB) (see Table 2 and 3 of EN ISO 20345:2011): all
	SRC = Slip resistance – meets the following requirement:	
	 <u>surface</u>: ceramic / <u>lubricant</u>: detergent <u>surface</u>: steel / <u>lubricant</u>: glycerol. 	solution;
	Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011):	
	\$3 = closed seat region, antistatic properties, energy absorption of seat region resistance to fuel oil, water penetration resistance and absorption (water-repellen upper), penetration resistance, cleated outsole; CI = cold insulation of the outsole.	
	opper,, penerranon resistance, ciedrea c	outsole, CI - Cold insulation of the outsole.
		othetic stitch proof insole tends to decrease with the the synthetic insole offers more protective surface and burnicity and impact absorption).
	Note 2: the footwear also meets the requirement	ent in accordance with IEC 61340-5-1:2016 (I <mark>EC</mark> 61340-
	4-3:2017) for the electrical resistance ESD (elec	ctric dissipative tootwear).
Marking:	on a stitched label and displaying the fol - CE Marking;	lowing information:
	- registered trademark, name and comp	
	designation of the footwear (= article rnr. and year of the Standard of referen	
	- size of the footwear (printed on the out	
	production date (month + year);additional information: website, catego	





DBD No 0330 B

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2021/06/30 n. **860212605/TE** Validity: 2026/06/29



bon t wony... be nappy.

www.u-power.it

UGROUP RS20224

05/2021 RICK ESD

EN ISO 20345:2011 S3 CI SRC

MADE IN TUNISIA

UGROUP SRL Via Borgomanero,50 Paruzzaro (NO)-Italy

DPI II



SECOSOL® COMPLETE 951622012451XX



SECOSOL® LAMINATO CON TESSUTO 9516101XXX7XXX



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements.

The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded a upon request.

The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

