

PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





## EU Type Examination Certificate

Date: 2021/01/26

## n. 860210406/TE

Validity: 2026/01/25

This Certificate is a translation in English of the original Certificate issued in Italian.

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the	<b>U-GROUP SRL</b> Via Borgomanero, 50 – 28040 Paruzzaro (NO) – Italia		
PPE)			
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials)		
Category of PPE:	II : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.		
Model	"OXFORD"		
	code <b>UW20094</b>		
Description:	<u>model</u> : A (low footwear); <u>fastening system</u> : by means of laces; <u>processing</u> : direct injection;		
Ning and Sol	outsole: black compact PU "7466 INDUSTRY" marked "ANTISTATIC OIL RESISTANT" (CF 00006); midsole: black foam PU (CH 00007);		
	upper: black coated microfiber (SI 00233) with insert made of silver synthetic retro reflective material GRANA CARBON SINT. (PL 00002) in the heel area; tongue and bellows: black fabric ALBANY semplice (SI 00046), centrally padded and		
	lined; <u>vamp lining</u> : grey three-dimensional fishnet knitting OMEGA ECO C02 (SI 00120); <u>quarter and tongue lining</u> : col. 27 grey three-dimensional fishnet knitting IMOLA (S 00168);		
	insole: white multi-layered fabric with black print declared conductive art. WB FLE (code SP 00007), which also serves as penetration resistant insert; removable insock: black perforated foam material MEMORY coupled with black knittin		
	in contact with the foot, with zig-zag stitching with conductive thread in the forepart (T 00153); <u>toecap</u> : made of polymeric material, article PS240 HAWAI (PU 00042).		
	Optional interchangeable orthopedic insocks (DGUV 112-191) described by the Customer as follows (see also page 3): SECOSOL® by Matthias Hartmann Orthopädie + Sport GmbH (max thickness in the toetip area: 2,9 mm): SECOSOL® COMPLETE – article number 951622012451XX		
	SECOSOL® LAMINATO CON TESSUTO – article number 9516101XXX7XXX		
Technical Standard:	EN ISO 20344:2011 Personal protective equipment – Test methods for footwea (UNI EN ISO 20344:2012)		
	EN ISO 20345:2011 Personal protective equipment – Safety footwear (UNI EN ISO 20345:2012)		
	general industry, engineering industry, agriculture, warehouses, works on trucks, cranes.		



PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





TUTIT

## EU Type Examination Certificate

Size range:       from 35 to 48         Technical File:       DC-12713/E         Test report:       RCT n°394715         Functions and performance level:       basic requirements for safety footwear (SB) (see Table 2 and 3 of EN ISO 20345:20) impacts and anotation on same site following requirement: - surface: certaine / lubricant: detergent solution; - surface: seteet / lubricant: detergent solution; - surface: seteet / lubricant: diversion.         S3 = closed sect region, antistatic properties, energy absorption of sect n queet, penetration resistance of the synthetic sitch proof insole tends to decrease w demeter of the penetration resistance of the synthetic sitch proof insole tends to decrease w demeter of the penetration resistance and absorption.         Marking:       on a sitched label and displaying the following information: - CE Marking: - registered fractement, name and complete address of the Manufacturer: - designation of the footwear (printed on the outspot): - nr. and year of the Standard of reference + safety symbols: - side of the footwear (printed on the outspot): - nr. and year of the Standard of reference + safety symbols: - additional information: website, category of the PPE, "Made in".	Date: 2021/01/26	n. 860210406/TE	Validity: 2026/01/2
Test report:       RCT n'3934715         Functions and performance levels:       basic requirements for safety footwear (SB) (see Table 2 and 3 of EN ISO 20345:20) mandatory ones, among which:         SRC = Slip resistance - meets the following requirement: - surface: ceramic / lubricant: detergent solution; - surface: steel / lubricant: glycerol.         Additional requirements [7db. 18 and 20 of EN ISO 20345:2011]: S3 = closed seat region, antistatic properties, energy absorption of seat n resistance to tuel oil, water penetration resistance and absorption (water-rep upper), penetration resistance of the synthetic stick proof insole tends to decrease w diameter of the performing object; in return the synthetic insole offers more protective surface ergonomics advandages (flexibility, insulation, humdity and impact absorption).         Marking:       on a stitched label and displaying the following information: - CE Marking; - registered trademark, name and complete address of the Manufacturer; - designation of the tootwear (a raticle name and alphanumeric code); - nr. and year of the Standard of reference + safety symbols: - size of the footwear (anited on the outsole); - production date (month + year); - additional information: website, category of the PPE, "Made in".	Size range:	from 35 to 48	
Functions and performance levels:       basic requirements for safety footwear (SB) (see Table 2 and 3 of EN ISO 20345:201 mandatory ones, among which:         SRC = Slip resistance – meets the following requirement:       - surface; ceramic / lubricant; dycerol.         Additional requirements [Tab. 18 and 20 of EN ISO 20345:2011):       S3 = closed seat region, antistatic properties, energy absorption of seat in resistance to fuel oil, water penetration resistance and absorption (water-regupper), penetration resistance, cleated outsole.         Note: the penetration resistance of the synthetic sitch proof insole tends to decrease widdometer of the performing object; in return the synthetic insole offers more protective surface regiononics advantages (flexibility, insulation, humidity and impact absorption).         Marking:       on a stitched label and displaying the following information:         - CE Marking:       - registered frademark, name and complete address of the Manufacturer;         - designation of the footwear (printed on the outsole);       - production det (month + year);         - production date (month + year);       - additional information: website, category of the PPE, "Made in".	Technical File:	DC-12713/E	
performance levels: mandatory ones, among which:           SRC = Slip resistance – meets the following requirement:           - surface: ceramic / µbricant: detergent solution;           - surface: steel / µbricant: detergent solution;           - gentarian resistance of the synthetic stitch proof insole tends to decrease w           diameter of the performing object; in refurnt the synthetic insole offers more protective surface           ergenomics advantages (flexibility, insulation, humidity and impact detergent solution;           - registered trademark, name and complete address of the Manufacturer;           - designation of the footwear (printed on the outsole);           - production date (month	Test report:	RCT n°3934715	
<ul> <li>surface: ceramic / lubricant: glycerol.</li> <li>auface: steel / lubricant: glycerol.</li> <li>Additional requirements (Tab. 18 and 20 of EN ISO 20345;2011):</li> <li>S3 = closed seat region, antistatic properties, energy absorption of seat n resistance to fuel oil, water penetration resistance and absorption (water-regupper), penetration resistance, cleated outsole.</li> <li>Note: the penetration resistance of the synthetic sitch proof insole tends to decrease with a diameter of the performation object in retrut the synthetic insole offers more protective surface: genomics advantages (flexibility, insulation, humidity and impact absorption).</li> <li>Marking:</li> <li>on a stitched label and displaying the following information:         <ul> <li>CE Marking:</li> <li>registered trademark, name and complete address of the Manufacturer;</li> <li>designation of the footwear (= article name and alphanumeric code);</li> <li>nr. and year of the Standard of reference + safety symbols;</li> <li>size of the footwear (printed on the outsole);</li> <li>production date (month + year);</li> <li>additional information: website, category of the PPE, "Made in",</li> </ul> </li> </ul>			nd 3 of EN ISO 20345:2011): c
<ul> <li>S3 = closed seat region, antistatic properties, energy absorption of seat r resistance to fuel oil, water penetration resistance and absorption (water-regupper), penetration resistance, cleated outsole.</li> <li>Note: the penetration resistance of the synthetic sitch proof insole tends to decrease widameter of the perforating object; in return the synthetic insole offers more protective surface ergonomics advantages (flexibility, insulation, humidity and impact absorption).</li> <li>Marking: On a stitched label and displaying the following information: <ul> <li>CE Marking:</li> <li>registered frademark, name and complete address of the Manufacturer:</li> <li>designation of the footwear (= article name and alphanumeric code);</li> <li>nr. and year of the Standard of reference + safety symbols;</li> <li>ize of the footwear (printed on the outsole);</li> <li>production date (month + year);</li> <li>additional information: website, category of the PPE, "Made in".</li> </ul> </li> </ul>		<ul> <li><u>surface</u>: ceramic / <u>lubricant</u>: detergent solution;</li> </ul>	
diameter of the perforating object; in return the synthetic insole offers more protective surface ergonomics advantages (flexibility, insulation, humidity and impact absorption). Marking: • CE Marking: • registered trademark, name and complete address of the Manufacturer; • designation of the footwear (a riticle name and alphanumeric code); • nr. and year of the Standard of reference + safety symbols; • size of the footwear (printed on the outsole); • production date (month + year); • additional information: website, category of the PPE, "Made in",		<b>S3 =</b> closed seat region, antistatic properties, energy resistance to fuel oil, water penetration resistance and	absorption of seat regio
<ul> <li>CE Marking;</li> <li>registered trademark, name and complete address of the Manufacturer;</li> <li>designation of the footwear (= article name and alphanumeric code);</li> <li>nr, and year of the Standard of reference + safety symbols;</li> <li>size of the footwear (printed on the outsole);</li> <li>production date (month + year);</li> <li>additional information: website, category of the PPE, "Made in".</li> </ul>		diameter of the perforating object; in return the synthetic insole of	fers more protective surface ar
		<ul> <li>CE Marking;</li> <li>registered trademark, name and complete address of the</li> <li>designation of the footwear (= article name and alphanu</li> <li>nr. and year of the Standard of reference + safety symbol</li> <li>size of the footwear (printed on the outsole);</li> <li>production date (month + year);</li> </ul>	e Manufacturer; imeric code); ls;
States and States			
Storean Storean			
O. P.O.			COLLAU Bonismo Www.corre



PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





## EU Type Examination Certificate

Date: 2021/01/26

n. 860210406/TE

Validity: 2026/01/25



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).



Certificato ue E rev05 - 26/10/20

3/3